

The photograph may not match the reference exactly. Please read the product description to identify the finish.

Download photometric file .ldt /.ies

TECHNICAL CHARACTERISTICS

Type:	Ceiling fixture
IP Protection degrees:	IP40
Light source 1:	60 x LED Vossloh 26,1W Neutral white - 4000K 3190 lm ^(N) CRI 80
Voltage / Frequency:	220-240V/50-60Hz
Warranty (Years):	2
Option to extend the guarantee (Years):	5



MATERIALS / FINISHES

Structure material:	Aluminium	Diffuser material:	Polycarbonate
Structure finish:	Grey	Diffuser finish:	Tinted

GEAR

Gear included: Yes, electronic

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.


LEDS-C4 reserves the right to make the necessary technical changes they deem adequate, in order to improve the features of the product.

Please consult the sales team to clarify any doubt.

Luminaire		Measur.		Lamp			
Code	15-5469-14-OS	Code	15-5469-14-OS	Code	15-5469-14-OS		
Name	Plafón INFINITE 60 leds 26.1W	Name	Plafón INFINITE 60 leds 26.1W	Number	1		
Line	- LEDS C4 LEDS	Date	02-02-2016	Position	Universal		
Luminaire Flux	2227.96 lm	Luminaire Power	26.00 W	Efficacy	85.69 lm/W	Efficiency	100.00%
Lamps Flux	2227.96 lm	Maximum value	916.93 cd	Position	C=0.00 G=0.00	CG Double Symmetrical	
Rectangular Luminaire		Length	855 mm	Width	50 mm	Height	80 mm
Rectangular Luminous Area		Length	840 mm	Width	45 mm	Height	0 mm
Horizontal Luminous Area	0.037800 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.009145 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		02-02-2016		Maximum Gamma Angle	90		
Measurement Distance		6.44		Measurement Flux	2227.96 lm		
Operator		Asselum T2		Source voltage	230.00 V		
Temperature		24.00 °C		Source current			
Humidity		52.00 %		Photocell	Prc		
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
- LEDS C4 LEDS	15-5469-14-OS	Name Lámpara 60 leds 26.1W	2227.96	26.00	1
C.I.E.	52 82 96 100 100	D DIN 5040	A40		
F UTE	1.00 D	B NBN	BZ 4		

855mm x 50mm



C Halfplanes
 180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

