

DASAR 180 PREMIUM

outdoor inground fitting, LED, 3000K, IP67, round, bezel stainless steel, 60°, Ø/H 17.7/12.71 cm, 24W



| | |
|---------------------------|--|
| Article number | 233756 |
| Max. wattage | 24 Watt |
| Light distribution type 1 | Direct |
| Feed-in capability | No |
| Lamp included | No |
| Installation diameter | 15.6 cm |
| Installation depth | 16.4 cm |
| Depth | 12.7 cm |
| Diameter | 17.7 cm |
| Net weight | 2.65 kg |
| Gross weight | 3.18 kg |
| Voltage | 220-240 ~50/60 . 750 Volts |
| Protection class | I |
| IP-rating | IP 67 |
| Beam angle | 38 Degree |
| Material | Aluminium / Stainless steel 316L / Glass |
| Colour | Stainless steel |
| Way of mounting | Recessed floor |
| Average lifespan | 30000 Hours |
| Colour temperature | 3000 Kelvin |
| Colour rendering index | 80 |
| Luminous flux | 3260 lm |
| Energy efficiency class | A++ |
| fastCalcEnabled | No |
| ranking | 400 |
| Catalogue page | BIG WHITE 2017: 716 |

The walk-on and scratch resistant high-voltage surface-mounted floor light DASAR 180 PREMIUM with its round stainless-steel bezel and glass cover is fitted with warm-white, high-performance power LEDs. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly. In addition, the luminaire has high thermal, chemical, mechanical and optical resistance. There are other versions of the luminaire with different beam angles or, alternatively, with a stainless steel housing available. This luminaire contains built-in LED lamps. EEI A - A++ The lamps in the luminaire cannot be replaced.